

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Workstation CELSIUS C740

1U Performance from Virtually Anywhere

Driven by German precision engineering and innovation, Fujitsu's engineers maximized rack density in the datacenter while at the same time offering true workstation performance in only 1U. This allows customers in the automotive, aeronautic, broadcasting, energy as well as healthcare industry to benefit from faster time-to-market and reduced innovation cycles from the safety of the datacenter.



Manageability

Server based management in a rack workstation

- Windows® Server 2012 R2
- The integrated Remote Management Controller iRMC S4 allows comprehensive control, irrespective of the system status
- ServerView embedded Lifecycle Management (eLCM) offers image management and enables LAN enhanced security and stability in a fully automated environment
- Easy to set-up

Energy efficiency

Fujitsu's Cool-safe® Advanced Thermal Design technology for a broader range of ambient temperature

- Temperatures in the data center can now vary between 5 °C and 40 °C
- Benefits: cost savings and optimization potential

Best visualization - even virtualized

Meeting your demands as a 1:1 remote workstation, a 1:n virtualized workstation or even a node in a render cluster

- Support of up to two high-end graphic cards (single height) or one ultra-high-end graphic card (double height)
- Up to 512 GB DDR4 (2400 MHz) memory

Storage Flexibility

Comprehensive choice of storage solutions

- SATA DOM: Disk-On-Module with SSD performance i.e. for booting your hypervisor
- Fujitsu PCIe SSD: Choice of on-board or PCIe card solution for maximum I/O performance
- SATA SSD: High-speed SATA SSDs



RADEON PRO WX

Components

| | |
|---|--|
| Processor | Intel® Xeon® processor E5-2699v4 (22 cores, 2.20 GHz, 55 MB) |
| | Intel® Xeon® processor E5-2697v4 (18 cores, 2.30 GHz, 45 MB) |
| | Intel® Xeon® processor E5-2697Av4 (16 cores, 2.60 GHz, 40 MB) |
| | Intel® Xeon® processor E5-2690v4 (14 cores, 2.60 GHz, 35 MB) |
| | Intel® Xeon® processor E5-2680v4 (14 cores, 2.40 GHz, 35 MB) |
| | Intel® Xeon® processor E5-2650v4 (12 cores, 2.20 GHz, 30 MB) |
| | Intel® Xeon® processor E5-2643v4 (6 Cores, 3.40 GHz, 20 MB) |
| | Intel® Xeon® processor E5-2640v4 (10 Cores, 2.40 GHz, 25 MB) |
| | Intel® Xeon® processor E5-2637v4 (4 Cores, 3.50 GHz, 15 MB) |
| | Intel® Xeon® processor E5-2630v4 (10 Cores, 2.20 GHz, 25 MB) |
| | Intel® Xeon® processor E5-2623v4 (4 Cores, 2.60 GHz, 10 MB) |
| | Intel® Xeon® processor E5-2620v4 (8 Cores, 2.10 GHz, 20 MB) |
| | Intel® Xeon® processor E5-2609v4 (8 Cores, 1.70 GHz, 20 MB) |
| | Intel® Xeon® processor E5-2603v4 (6 Cores, 1.70 GHz, 15 MB) |
| | Intel® Xeon® processor E5-1680v4 (8 Cores, 3.40 GHz, 20 MB) |
| | Intel® Xeon® processor E5-1660v4 (8 Cores, 3.20 GHz, 20 MB) |
| | Intel® Xeon® processor E5-1650v4 (6 Cores, 3.60 GHz, 15 MB) |
| | Intel® Xeon® processor E5-1630v4 (4 Cores, 3.70 GHz, 10 MB) |
| | Intel® Xeon® processor E5-1620v4 (4 Cores, 3.50 GHz, 10 MB) |
| | Intel® Xeon® processor E5-1607v4 (4 Cores, 3.10 GHz, 10 MB) |
| Intel® Xeon® processor E5-1603v4 (4 Cores, 2.80 GHz, 10 MB) | |
| Operating systems | |
| Operating system pre-installed | Windows 10 Pro Windows 7 Professional (available through downgrade rights from Windows 10 Pro) |
| Operating system compatible | Windows 8.1 Pro 64-bit (available through downgrade rights from Windows 10 Pro) Windows® Server 2012 Linux |
| Operating system notes | Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server |
| Memory modules | |
| | 8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,400 MHz |
| | 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,400 MHz |
| | 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,400 MHz |
| | 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,400 MHz |

Graphics

| |
|---|
| Ultra-high-end 3D: NVIDIA® Quadro® GV100, 32 GB, PCIe x16, 4 x DisplayPort |
| Ultra-high-end 3D: NVIDIA® Quadro® P6000, 24 GB, PCIe x16, 1x Dual Link DVI-D, 4 x DisplayPort |
| Ultra-high-end 3D: NVIDIA® Quadro® P5000, 16 GB, PCIe x16, 1x Dual Link DVI-D, 4 x DisplayPort |
| High-end 3D: AMD FirePro™ W7100, 8 GB, PCIe x16, 4 x DisplayPort |
| High-end 3D: AMD Radeon™ Pro WX 7100 , 8 GB, PCIe x16, 4 x DisplayPort |
| High-end 3D: NVIDIA® Quadro® P4000, 8 GB, PCIe x16, 4 x DisplayPort |
| Midrange 3D: NVIDIA® Quadro® P2000, 5 GB, PCIe x16, 4 x DisplayPort |
| Midrange 3D: AMD Radeon™ Pro WX 5100, 8 GB, 320 stream processors, PCIe x16, 4 x DisplayPort |
| Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4x miniDP |
| Entry 3D: AMD Radeon™ Pro WX 3100, 4 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP |
| Entry 3D: NVIDIA® Quadro® P600, 2 GB, PCIe x16, 4x miniDP |
| Entry 3D: AMD Radeon™ Pro WX 2100, 2 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP |
| Entry 3D: NVIDIA® Quadro® P620, 2 GB, PCIe x16, 4x miniDP |
| Entry 3D: NVIDIA® Quadro® P400 , 2 GB, PCIe x16, 3x miniDP |
| Professional 2D: NVIDIA® NVS™ 510, 2 GB, 16 cores, PCIe 2.0 x16, 4x miniDP, 4x miniDP/DP Adapter |
| Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 1x LFH59 (max. 2x DP or 2x DVI-I) |
| Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP |
| Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP |

Personal Supercomputing

Coprocessor: NVIDIA® Tesla® M60, 16 GB, 4096 cores, PCIe x16

Hard disk drives (internal)

| |
|---|
| SSD PCIe, 1024 GB M.2 NVMe Highend module |
| SSD PCIe, 512 GB M.2 NVMe Highend module |
| SSD PCIe, 256 GB M.2 NVMe Highend module |
| SSD PCIe, 2x 1024 GB M.2 NVMe Highend card |
| SSD PCIe, 2x 512 GB M.2 NVMe Highend card |
| SSD PCIe, 2x 256 GB M.2 NVMe Highend card |
| SSD PCIe, 1x1024 GB M.2 NVMe Highend card |
| SSD PCIe, 1x 512 GB M.2 NVMe Highend card |
| SSD PCIe, 1x 256 GB M.2 NVMe Highend card |
| SSD PCIe, 1x 1024 GB M.2 NVMe card |
| SSD PCIe, 1x 512 GB M.2 NVMe card |
| SSD PCIe, 1x 256 GB M.2 NVMe card |
| SSD SATA III, 960 GB High Endurance, 3DWPD, 2.5-inch |
| SSD SATA III, 960 GB High Endurance, 1DWDP, 2.5-inch |
| SSD SATA III, 480 GB High Endurance, 3DWPD, 2.5-inch |
| SSD SATA III, 480 GB High Endurance, 1DWDP, 2.5-inch |
| SSD SATA III, 240 GB High Endurance, 3DWPD, 2.5-inch |
| SSD SATA III, 240 GB High Endurance, 1DWDP, 2.5-inch |
| SSD SATA III, 1024 GB, 2.5-inch |
| SSD SATA III, 512 GB, 2.5-inch |
| SSD SATA III, 256 GB, 2.5-inch |
| SSD SATA III, 128 GB, 2.5-inch |
| SSD SATA III, 256 GB, 2.5-inch, SED |
| HDD SAS, 10,000 rpm, 1800 GB, 2.5-inch |
| HDD SAS, 10,000 rpm, 1200 GB, 2.5-inch |
| HDD SAS, 10,000 rpm, 900 GB, 2.5-inch |
| HDD SAS, 10,000 rpm, 600 GB, 2.5-inch |
| HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical |
| HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical |
| HDD SATA III, 7,200 rpm, 1000 GB, 2.5-inch, enhanced availability |

| | |
|---|--|
| Hard disk notes | *Disk imaging software of the customer must be 4k sector size / advanced format ready One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. 24/7 ready (business critical HDDs required) Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SED (Self-Encrypting Drive) SSD (Solid State Disk) |
| Drives (optional) | DVD Super Multi ultra slim (tray) |
| SCSI / SAS Controller | LSI RAID Ctrl SAS 1GB (D3216) RAID 5/6 Ctrl. 12 Gbit/s 8 ports int. LSI RAID Ctrl SAS (D3327) RAID 0/1 Ctrl. 12 Gbit/s 8 ports int. |
| Interface add on cards/components (optional) | Serial Interface FH PLAN EP X550-T2 2x10GBASE-T Gigabit Ethernet PCIe x1 Dual 10 Gigabit Ethernet PCIe x8 |
| Base unit | CELSIUS C740 (S26361-K1448-V125) |
| Mainboard | |
| Mainboard type | D3288-A2 |
| Formfactor | proprietary |
| Chipset | Intel® C612 |
| Processor socket | LGA 1155 |
| Processor quantity maximum | 1 |
| Supported capacity RAM (max.) | 512 GB |
| Memory slots | 8 DIMM (DDR4) ECC |
| Memory frequency | 2,400 MHz |
| Memory notes | Quad channel support. For quad channel performance, a minimum of 4 memory modules have to be ordered. Capacity per channel has to be the same. |
| LAN | 2x Built-in 10/100/1,000 MBit/s Intel® I217LM and Intel® I210AT |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) |
| I/O controller on board | |
| Serial ATA total | 6 |
| thereof SATA III | 6 |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 |
| SATA RAID support | 0, 1, 10, 5 |
| Interfaces | |
| USB 2.0 total | 2 |
| USB 3.1 Gen1 (USB 3.0) total | 2 |
| USB front | 2x 2.0 |
| USB rear | 2x 3.0 |
| USB internal | 1x 3.0 |
| VGA | 1 (IRMC) |
| Serial (RS-232) | 1 (optional via slot bracket) |
| Ethernet (RJ-45) | 2 |

Input device / components

| | |
|--------------------------|--|
| Input devices (optional) | Optical USB tilt wheel mouse Keyboard |
|--------------------------|--|

Drive bays

| | |
|-------------------------|---|
| Drive bays total | 5 |
| 2.5-inch internal bays | 4 |
| 5.25-inch external bays | 1 |
| Drive bay notes | Up to 4x 2.5-inch HDDs/SSDs (cold plug) |

Slots

| | |
|--------------------------------|--|
| PCI-Express 3.0 x8 (mech. x16) | 1 Full height (single slot density) |
| PCI-Express 3.0 x16 | 1 x (340 mm / 13.39 inch) Full height (double slot density) or 2 x (340 mm / 13.39 inch) Full height (single slot density) |

Electrical values

| | |
|------------------------------------|--|
| Power efficiency note | power supply efficiency (at 230V; 20% / 50% / 100% load) : 90% / 94% / 92% |
| Rated voltage range | 100 V - 240 V (AC Input) |
| Rated frequency range | 47 Hz - 63 Hz |
| Operating voltage range | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | 800 W |
| Power supply output | 800 W |

Dimensions / Weight / Environmental

| | |
|-------------------------------|---|
| Dimensions (W x D x H) | 431 x 683 x 44.45 mm 16.97 x 26.89 x 1.75 inch |
| Operating position | Horizontal / vertical (I/O ports facing down) |
| Weight | approx. 13 kg |
| Weight (lbs) | approx. 28.7 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating relative humidity | 5 - 85 % (relative humidity) |

Compliance

| | |
|-----------------|--|
| Product | CELSIUS C740 |
| Model | CR1U |
| Europe | CE Class A* |
| USA/Canada | FCC Class A |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |

Additional Software

| | |
|------------------------------------|---|
| Additional software (preinstalled) | Nero Essentials S (burning software) Fujitsu Recovery (hard disk based recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft Office (buy license to activate the pre-installed Microsoft Office) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero 10 Essentials XL (burning/backup/DVD-playback suite) |

| Security | |
|---|--|
| System and BIOS Security | EraseDisk Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 2.0) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password |
| Manageability | |
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT Intel® Active Manageability Technology v8.0 (not activated, not set up) |
| Manageability software | DeskView 10.x client management including: |
| DeskView components | On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN) |
| Manageability link | http://www.fujitsu.com/fts/manageability http://www.fujitsu.com/fts/solutions/high-tech/solutions/workplace/manageability/feature-finder.html |
| Packaging information | |
| Packaging dimension (mm) | 264 x 490 x 87 mm |
| Packaging dimension (inch) | 10.39 x 19.29 x 3.43 inch |
| Max. quantity / pallet | 12 |
| Packaging notes | printed user documentation is bleached in chlorine free process |
| Warranty | |
| Warranty period | 3 years (depending on country) |
| Warranty type | Onsite Service |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Product Related Services - the perfect extension | |
| Recommended Service | - 9x5, Onsite Response Time: Next Business Day |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |

Recommended Accessories

FUTRO L420



The FUJITSU FUTRO L420 meets a multitude of user and business needs. It is designed to handle standard office tasks and demanding, high-graphics applications over PCoIP. Dual-monitoring enables you to increase your productivity. As a smart zero client, the FUJITSU FUTRO L420 provides high security, easy management and zero noise, whilst being user-friendly and integrating easily into an existing VMware® network.

Order Code:
S26361-K1062-V200

FUTRO L620



The FUJITSU FUTRO L620 meets a multitude of user and business needs. It is designed to handle standard office tasks and demanding, high-graphics applications over PCoIP. Quad-monitoring enables you to increase your productivity. As a smart zero client, the FUJITSU FUTRO L620 provides high security, easy management and zero noise, whilst being user-friendly and integrating easily into an existing VMware® network.

Order Code:
S26361-K1062-V300

More information

Fujitsu products, solutions & services

In addition to the FUJITSU Workstation CELSIUS C740, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Workstation CELSIUS C740, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-09-03 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH