

Data Sheet

FUJITSU JX60 S2 DAS Subsystem

High-capacity Direct Attached Storage (DAS) subsystem



FUJITSU JX DAS Subsystem

Data centers today are evolving, adopting new technologies to meet the demands of digital transformation. This has contributed to an enormous increase in the amount of data created. As data grows, the storage requirements may exceed beyond the internal storage capacity of servers, affecting server performance. So the need to quickly and efficiently meet the growing server storage needs is more than ever.

Direct-attached storage (DAS) system offers a simple solution for storage expansion by directly attaching storage subsystems to the server via a host interface. FUJITSU JX DAS Subsystem offers a perfect DAS solution for PRIMERGY Servers that seamlessly extend server storage capacity in an easy and cost-effective way. FUJITSU JX DAS Subsystem provides fast time to value and are highly flexible with support for mixed storage device configurations. With support for fully redundant components and multiple RAID levels, it ensures high level of availability and reliability.

JX60 S2 DAS Subsystem

FUJITSU JX60 S2 DAS Subsystem provides high storage device capacity in a 4U Enclosure. It can support up to 60 x 3.5 inch disk drives, delivering a capacity of up to 720 Terabytes (2.5 inch devices can be installed in the same slot as the 3.5 inch devices using 3.5 inch mounting frames that are provided). A total capacity of 1,440 Terabytes can be delivered by attaching up to 2 enclosures directly to a server. It is integrated with FUJITSU Software ServerView Suite for easy management and control. It is ideal for enterprises looking for high capacity storage solution including virtualization, Microsoft Exchange server or HPC workloads etc.



Features & Benefits

| Main Features | Benefits |
|---|---|
| <p>Performance and flexibility</p> <ul style="list-style-type: none"> ■ Direct Attached Storage (DAS) for PRIMERGY and other x86 industry-standard servers with 12 Gbit/s SAS connection ■ Up to 120 large capacity Nearline SAS storage devices, expand storage capacity by up to 1,440 Terabyte <p>Quality and reliability</p> <ul style="list-style-type: none"> ■ Components like hot-plug disk drives and power supply modules can be replaced while the server is running ■ The redundant hot-plug power supply units can be connected with phase redundancy via separate power lines ■ Optimum and secure cooling of the drives is ensured by two independent fans <p>Ease of use</p> <ul style="list-style-type: none"> ■ Flexible and modular components for easy deployment and management ■ Status of the component is signalized by LC displays and LEDs ■ Disk drive extension is completely managed by the server (connected to HBA/RAID card installed into servers) and can be used in all usage scenarios with certified PRIMERGY servers ■ Integrated with standard FUJITSU Software ServerView Suite | <ul style="list-style-type: none"> ■ Reliable storage capacity for biggest data volume ■ Flexible configuration options: capacity optimized or speed-optimized ■ Hot-swap devices and hot-swap/redundant power supplies provide maximum uptime ■ Continuous operation during flexible disk drive replacements ■ Seamless Integration with PRIMERGY Servers ■ Easy installation and control of the subsystem |

Technical details

| | |
|--------------------------------------|--|
| Supported RAID levels | 0, 1, 1+0, 5, 5+0, 6, 6+0 |
| Host Interfaces | SAS 3.0 I/O-module (expander) |
| Connector Type | 1 Port MiniSAS HD (SFF-8644) |
| Supported PRIMERGY server controller | Fujitsu PSAS CP400e SAS Controller Fujitsu PRAID EP420e |
| Maximum Storage Capacity | 1,440 (Cascading) TB |
| Drive Type | 3.5-inch, Nearline SAS, 7,200 rpm (12 TB / 10 TB / 8 TB / 6 TB / 4 TB / 2 TB) 3.5-inch, SAS, 10,000 rpm (1.2 TB / 900 GB) 2.5-inch, SAS, 15,000 rpm (600 GB / 300 GB) 2.5-inch, SSD (1.92 TB / 960 GB / 1.6 TB / 800 GB / 400 GB) |
| Drive interface | Serial Attached SCSI (12 Gbit/s) |
| Management | |
| Administration | Web-based graphical user interface |
| Installation specification | |
| 19" rackmount | Yes |
| Dimension - per rack (W x D x H) | 482 x 980 x 176 mm 19 x 38.6 x 6.9 inch |
| Height Unit standard | 4 U |
| Height Unit Maximum | 8 U |
| Weight | max. 100 kg (depending on the number of installed disks) |
| Service Area | Front: 800 mm (31.5 inch) or more Rear: 800 mm (31.5 inch) or more |
| Power voltage | AC 100 - 120 V / AC 200 - 240 V |
| Power frequency | 50 / 60 Hz |
| Power supply efficiency | 92 % (80 PLUS gold) |
| Maximum Power Consumption | AC 100 - 120 V: 1300 W (1320 VA) |
| Maximum Power Consumption | AC 200 - 240 V: 1300 W (1320 VA) |
| Power phase | Single (phase redundancy possible) |
| Environment | |
| Maximum Heat Generation | AC 100 - 120 V: 4700: kJ/h AC 200 - 240 V: 4700: kJ/h |
| Temperature (not operating) | 0 - 50 °C |
| Humidity (operating) | 20 - 80 % (relative humidity, non-condensing) |
| Humidity (not operating) | 8 - 80 % (relative humidity, non-condensing) |
| Altitude | 3,000 m (10,000 ft.) |
| Sound pressure (LpAm) | 43.5 dB(A) |
| Sound power (LWAd; 1B = 10dB) | 6.0 B |
| Noise notes | measured according to ISO7779 and declared according to ISO9296 |
| Operating environment | FTS 04230 – Guideline for Data Center (installation specification) |
| Operating environment link | https://sp.ts.fujitsu.com/dmsp/Publications/public/FTS-04230-Specification-for-DataCenter.pdf |
| Compliance | |
| Product safety | UL 60950-1, CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1 |
| Electromagnetic Compatibility | CNS 13438, FCC Part-15 Class A, ICES 003 Class A, EN 55022 Class A, VCCI Class A, AS/NZS CISPR 22 Class A |
| Electromagnetic Immunity | EN 55024 |
| CE certification | 2004/108/EC, 2006/95/EC, 2011/65/EC |
| Approvals | CB, CE, C-Tick, EAC, FCC, VCCI |
| Environmental compliance | RoHS compliant, WEEE compliant |

Compliance

| | |
|-------------------------|---|
| Compliance notes | There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. |
|-------------------------|---|

| | |
|------------------------|---|
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
|------------------------|---|

Warranty

| | |
|------------------------|--------|
| Warranty period | 1 year |
|------------------------|--------|

| | |
|----------------------|-----------------|
| Warranty type | Onsite warranty |
|----------------------|-----------------|

| | |
|--|--|
| Warranty Terms & Conditions | www.fujitsu.com/support |
|--|--|

Product Related Services - the perfect extension

| | |
|-----------------------------|--|
| Support Pack Options | - Available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time (depending on country) 24x7, 4h Onsite Response Time (depending on country) |
|-----------------------------|--|

| | |
|----------------------------|----------------------------------|
| Recommended Service | - 24x7, Onsite Response Time: 4h |
|----------------------------|----------------------------------|

| | |
|--------------------------|-----------------------------------|
| Service Lifecycle | 5 years after end of product life |
|--------------------------|-----------------------------------|

| | |
|------------------------|--|
| Service Weblink | www.fujitsu.com/services/product-services |
|------------------------|--|

Fujitsu OPTIMIZATION Services

In addition to FUJITSU JX60 S2 DAS Subsystem, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu JX60 S2 DAS Subsystem, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/products

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2017 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.